



**MACINATORE / GRINDER / TRITURADOR  
TR 500 L – KW 9,2 / 11**

	<p>PARTICOLARE PLC PLC DETAIL DETALLE PLC</p>	
	<p>CENTRALINA OLEODINAMICA HYDRAULIC POWER UNIT CENTRAL HIDRÀULICA</p>	

POTENZA ELETTRICA ROTORE ROTOR ELECTRIC POWER POTENCIA ELECTRICA DEL ROTOR	kw	9,2 / 11
POTENZA ELETTRICA CENTRALINA PLC ELECTRIC POWER POTENZIA ELECTRICA PLC	kw	0,55
LUNGHEZZA ROTORE LENGHT ROTOR LONGITUD ROTOR	mm	470
DIAMETRO ROTORE ROTOR DIAMETER DIÁMETRO ROTOR	∅	260
GIRI AL ROTORE ROTOR ROTATIONS ROTACIONES DE ROTOR	rpm	50-70
LAME BLADES LÁMINAS	n° / D x D (*)	n° 22 / 30x30
TIPO DI LAMA TYPE OF BLADES TIPO DE LÁMINAS	i / p (**)	Incava / Piana
CORSA SPINTORE PUSHER RUN FUNCIONAMIENTO DEL EMPUJADOR	mm	350
LUNGHEZZA LENGHT LONGITUD	mm	1770
LARGHEZZA WIDTH ANCHO	mm	800
ALTEZZA DA TERRA HEIGHT ALTURA	mm	1600
LUNGH. BOCCA TRAMOGGIA HOPPER LENGHT LONGITUD DE LA TOLVA	mm	850
LARGH. BOCCA TRAMOGGIA HOPPER WIDTH ANCHURA DE LA TOLVA	mm	480
ALTEZZA TRAMOGGIA HOPPER HEIGHT ALTURA DE LA TOLVA	mm	690
PESO WEIGHT PESO	Kg	750

(\*) quantità x dimensione/quantity x dimension / cantidad x dimension (\*\*) incave/piane / i=incave/p=flat / i=concava/p=plana (\*\*\*) hollow / concava

**MILLER MAC SRLS**

Via G. Galilei 139/A, 35010 San Giorgio in Bosco (PD) - Italy

Tel. +39 0495996922 - Email: info@millermac.it – export@millermac.it - Web: www.millermac.it